

SIZE TABLE: QUANTITY OF SEGMENTS (UNITS) REQUIRED PER CENTRALIZER FOR VARIOUS PIPE, SCREEN, OR BAR DIAMETERS

<u>0.70 inch to 2.56 inch diameter</u>	
<i>GT Series (Includes GT 20-1, GT 30-1, GT 40-1)</i>	
Applications: Small diameter rock bolts, soil nails, drop pipe etc from 18mm up to 65mm diameter	
OD of Bar, Pipe or Screen etc	Units Required Per Centralizer
18mm - 29mm (0.70 inch - 1.14 inch)	2
29mm - 46mm (1.14 inch - 1.81 inch)	3
46mm - 65mm (1.81 inch - 2.56 inch)	4
Over 65mm (2.56 inch)	Use 155 HT Series
<u>2.28 inch to 7.09 inch diameter</u>	
<i>155 HT Series (Includes 155 HT-D, 155 HT-E)</i>	
Applications: Grouted casing, gravel packed screen, drop pipe, anchors etc with diameters greater than 58mm	
OD of Bar, Pipe or Screen etc	Units Required Per Centralizer
58mm - 90mm (2.28 inch - 3.54 inch)	2
90mm - 130mm (3.54 inch - 5.12 inch)	3
130mm - 180mm (5.12 inch - 7.09 inch)	4
Over 180mm (7.09 inch)	Use 380 HT Series
<u>6.30 inch and greater diameter</u>	
<i>380 HT Series (Includes 380 HT-D, 380 HT-E, 380 HT-F)</i>	
Applications: Grouted casing, gravel packed screen, drop pipe, cased crossings etc with diameters greater than 160mm	
OD of Bar, Pipe or Screen etc	Units Required Per Centralizer
160mm - 230mm (6.30 inch to 9.05 inch)	2
240mm - 340mm (9.45 inch to 13.39 inch)	3
340mm - 460mm (13.39 inch - 18.11 inch)	4
460mm - 580mm (18.11 inch - 22.83 inch)	5
580mm - 700mm (22.83 inch - 27.56 inch)	6
700mm - 800mm (27.56 inch - 31.50 inch)	7
Over 800mm (31.50 inch)	Refer Installation Guide